

PRODUCT SPECIFICATIONS FOR 938M



ENGINE

Maximum Gross Power	188 HP
Displacement(Standard Power Mode:Speed Range 1-3*)	427 in ³
Maximum Rated Gross Power - Maximum Engine Speed (Standard Power Mode:Range 1-3*)	1600 r/min
Rated Net Power - 1,800 rpm - SAE J1349 at Minimum Fan Speed (PerformancePower Mode:Range 1-4)	183 HP
Maximum Gross Torque - ISO 14396 (Standard Power Mode:Range 1-3*)	642 ft·lbf
Maximum Gross Power - 1,600 rpm - ISO 14396 (DIN) (Standard Power Mode:Range 1-3*)	176 mhp
Maximum Net Torque - SAE J1349 (PerformancePower Mode:Range 1-4)	649 ft·lbf
Maximum Gross Power - 1,800 rpm - ISO 14396 (PerformancePower Mode:Range 1-4)	188 HP
Rated Net Power - 1,600 rpm - ISO 9249 (DIN) at Minimum Fan Speed (Standard Power Mode:Range 1-3*)	172 mhp
Maximum Net Torque - SAE J1349 (Standard Power Mode:Range 1-3*)	627 ft·lbf

Rated Net Power - 1,800 rpm - ISO 9249 (DIN) at Minimum Fan Speed (PerformancePower Mode:Range 1-4) 186 mhp

Maximum Rated Gross Power - Maximum Engine Speed (PerformancePower Mode:Range 1-4) 1800 r/min

Maximum Gross Torque - ISO 14396 (PerformancePower Mode:Range 1-4) 664 ft·lbf

Displacement(PerformancePower Mode:SpeedRange 1-4) 427 in³

Maximum Gross Power - 1,800 rpm - ISO 14396 (DIN) (Performance Power Mode:Range 1-4) 190 mhp

Note (1) Net power ratings are tested at the reference conditions for the specified standard and denote power available at the flywheel when the engine is equipped with alternator, air cleaner, emission components and fan at specified speed.

Engine Model Cat C7.1 ACERT**

Rated Net Power - 1,600 rpm - SAE J1349 at Minimum Fan Speed (Standard Power Mode:Range 1-3*) 170 HP

Maximum Gross Power - 1,600 rpm - ISO 14396 (Standard Power Mode: Range 1-3*) 173 HP

Note (2) *Range 4 power and torque is equal to Performance Mode with Caterpillar Power by Range technology.

Note (3) **The Cat C7.1 ACERT engine meets Tier 4 Final/Stage V off-highway emission standards.

**Rated Net Power - 1,600 rpm - ISO
9249 at Minimum Fan Speed
(Standard Power Mode: Range 1-3*)** 170 HP

**Maximum Net Torque - ISO
9249:2007 (Standard Power Mode:
Range 1-3*)** 628 ft·lbf

**Rated Net Power - 1,800 rpm - ISO
9249 at Minimum Fan Speed
(Performance Power Mode: Range
1-4)** 184 HP

**Maximum Net Torque - ISO
9249:2007 (Performance Power
Mode: Range 1-4)** 650 ft·lbf

BUCKETS

Bucket Capacities 2.5-5 m³ (3.2-6.5 yd³)

Bucket Capacities - Light Material 3.1-5 m³ (4.0-6.5 yd³)

Bucket Capacities - General Purpose 2.5-3.2 m³ (3.2-4.2 yd³)

WEIGHTS

Operating Weight 35778 lb

CAB

ROPS ISO 3471:2008

FOPS ISO 3449:2008 Level II

Note (3) *The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Note (1) Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

Note (2)

The declared dynamic operator sound pressure levels per ISO 6396:2008*, when properly installed and maintained, are:

- Standard cab: 68 ±3 dB(A)
- Deluxe cab: 66 ±2 dB(A)

SERVICE REFILL CAPACITIES

Transmission - Gear Box	2.9 gal (US)
Engine Crankcase	5.3 gal (US)
Hydraulic System - Including Tank	44.9 gal (US)
Rear Axles	9.2 gal (US)
Front Axles	9.2 gal (US)
Diesel Exhaust Fluid (DEF) Tank	5 gal (US)
Note	DEF used in Cat SCR systems must meet the requirements outlined in the International Organization for Standardization (ISO) standard 22241-1.
Hydraulic Tank	23.8 gal (US)
Fuel Tank	51.5 gal (US)
Cooling System	7.9 gal (US)

LOADER HYDRAULIC SYSTEM

Note (1)

*3rd and 4th function flow is fully adjustable from 20% to 100% of maximum flow through the secondary display, when equipped.

Hydraulic Cycle Time - Performance Mode at 1,800 rpm - Raise, Ground Level to Maximum Lift	5.5 s
---	-------

**Hydraulic Cycle Time - Performance Mode at
1,800 rpm - Total Cycle Time** 9.7 s

Relief Pressure- Tilt Cylinder 4351 psi

**Hydraulic Cycle Time - Standard Mode at
1,600 rpm - Total Cycle Time** 10.6 s

**Maximum Working Pressure- Implement
Pump** 4061 psi

**Relief Pressure- Tilt Cylinder - 3rd and 4th
Function Maximum Working Pressure** 4061 psi

**Hydraulic Cycle Time - Standard Mode at
1,600 rpm - Dump, at Maximum Lift Height** 1.7 s

**Hydraulic Cycle Time - Performance Mode at
1,800 rpm - Dump, at Maximum Lift Height** 1.5 s

**Hydraulic Cycle Time - Standard Mode at
1,600 rpm - Raise, Ground Level to
Maximum Lift** 6.2 s

**Hydraulic Cycle Time - Performance Mode at
1,800 rpm - Float Down, Maximum Lift to
Ground Level** 2.7 s

**Maximum Flow - Implement Pump - 4th
Function Maximum Flow*** 42 gal/min

**Relief Pressure- Tilt Cylinder - 3rd and 4th
Function Relief Pressure** 4351 psi

**Hydraulic Cycle Time - Standard Mode at
1,600 rpm - Float Down, Maximum Lift to
Ground Level** 2.7 s

Maximum Flow - Implement Pump 50 gal/min

Maximum Flow - Implement Pump - 3rd Function Maximum Flow* 50 gal/min

STEERING

Maximum Working Pressure - Steering Pump	3500 psi
Steering Articulation Angle - Each Direction	40°
Maximum Flow - Steering Pump	34 gal/min
Number of Steering Wheel Turns - Full Left to Full Right or Full Right to Full Left	3.3 turns
Maximum Steering Torque - 0° (Straight Machine)	42506 ft·lbf
Maximum Steering Torque - 40° (Full Turn)	31398 ft·lbf
Steering Cycle Times - Full Left to Full Right - At 1,800 rpm: 90 rpm Steering Wheel Speed	2.3 s

TRANSMISSION

Forward and Reverse - Range 3	17 mile/h
Forward and Reverse - Range 4	25 mile/h
Note	*Creeper control allows maximum speed range adjustability from 1 km/h (0.6 mph) to 13 km/h (8 mph) in Range 1 through the secondary display, when equipped. Factory default is 7 km/h (4.4 mph).
Forward and Reverse - Range 1*	1-13 km/h (0.6-8 mph)
Forward and Reverse - Range 2	8 mile/h

SOUND

Note (1)

European Union Directive “2000/14/EC”

Average Exterior Sound Pressure (ISO 6395:2008)

101 dB(A)

Operator Sound Pressure (ISO 6396:2008)

72 dB(A)

TIRES

Note (1)

Other tire choices are available. Contact your Cat dealer for details.

Standard Size

20.5 R25, radial (L-3)

Note (2)

In certain applications, the loader’s productive capabilities may exceed the tire’s tonnes-km/h (ton-mph) capabilities.

Other Choices Include

20.5 R25, radial (L-2); 20.5 R25, radial (L-5); 20.5-25 12PR (L-2); 20.5-25 12PR (L-3); 20.5-25 16PR (L-5); 23.5 R25, radial (L-3); 650/65 R25 radial (L-3); Skidder/Agriculture; Solid Tires

Note (3)

Caterpillar recommends that you consult a tire supplier to evaluate all conditions before selecting a tire model.

AXLES

RearOscillating ± 11 degrees; Open differential (standard); Limited slip differential (optional)**Front**

Fixed; Locking differential (standard)

AIR CONDITIONING SYSTEM

Air ConditioningThe air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1.9 kg of refrigerant which has a CO₂ equivalent of 2.717 metric tonnes.

SUSTAINABILITY

Recyclability

94%

938M STANDARD EQUIPMENT

POWER TRAIN

Auto idle shut down feature

Cat C7.1 ACERT engine

- Power modes (Standard and Performance)
- Power by range (High Power in Range 4)
- Turbocharged and aftercooled
- Filtered crankcase breather
- Diesel particulate filter
- Selective Catalyst Reduction

Coded start (requires secondary display)

Coolant protection to -34° C (-29° F)

Enclosed wet disc full hydraulic brakes

Fuel priming pump, automatic

Hydraulically driven demand cooling fan

Hydrostatic transmission with electronic control

- Operator modes (Default, TC, Hystat, and Ice)
- Directional Shift Aggressiveness (fast, medium, slow)
- Rimpull control, adjust wheel torque
- Creeper control, adjust ground speed

Parking brake, electric

Single plane cooling package wide six fins per inch density

Throttle lock and max speed limiter

HYDRAULICS

Automatic lift and bucket kickouts, adjustable in-cab

Bucket and fork modes, adjustable in-cab

Cylinder damping at kickout and mechanical end stops

Fine mode control (fast, medium, slow) in fork mode

Hydraulic response setting (fast, medium, slow)

Hydraulic diagnostic connectors and S·O·SSM ports

Load sensing hydraulics and steering

ELECTRICAL

Alternator, 115 amp, heavy duty

12V power supply in cab (2)

Batteries, 1,000 CCA (2) 24V system, disconnect switch

Back-up alarm

Emergency shutdown switch

Halogen work and roading lights, LED rear tail lights

Product Link™ PRO with three year subscription

Remote jump start post

Resettable main and critical function breakers

OPERATOR ENVIRONMENT

75 mm (3 in) retractable seat belt, with audible alarm and indicator

Automatic temperature control

External heated mirrors with lower parabolic

Hydraulic control lockout

Interior cab lighting, door and dome
Interior rearview mirrors (2)
Lunch box storage
Radio ready speakers
Rear window defrost, electric
Seat-mounted electronic implement controls, adjustable
Column mounted multi function control – lights, wipers, turn signal
Tilt and telescopic steering wheel
Tinted front glass
Wet arm wiper/washer, 2-speed and intermittent, front

OTHER STANDARD EQUIPMENT

Large-access enclosure doors with adjustable close/open force
Parallel lift loader linkage

EU STANDARD EQUIPMENT

Deluxe cab
Secondary display
Rearview camera

938M OPTIONAL EQUIPMENT

OPTIONAL EQUIPMENT

Autolube, integrated in secondary display
Auxiliary flow, third and fourth function, adjustable through secondary display
Beacon light, strobe
Cab, deluxe (standard in Europe, optional in North America)
– Electrically adjustable external heated mirrors (2)
– Secondary display to enable features and adjust parameters
– Sunscreen, front and rear
Camera, rearview (standard in Europe)
Cold start package
Counterweight, (heavy and logger)
Coupler, (Fusion and ISO 23727)
Debris packages (low, medium, high)
Fenders (extended cover and full coverage)
Guarding (machine and operator)
Linkage, high lift
Lights, auxiliary, halogen or LED with engine and DEF compartment lights
Object Detection
Product Link ELITE with capabilities for software push, data logging, histogram and trend mapping
Radio packages
Ride Control System, adjustable through secondary display

Seats

- Deluxe seat – fully adjustable fabric air suspension seat with mid backrest and mechanical lumbar support
- Premium seat – fully adjustable leather and fabric air suspension with high backrest and air lumbar support. Seat is heated and ventilated on bottom cushion and backrest.

Steering

- Dual mode and secondary

NOTE: Not all features are available in all regions.